



NOTES:

1) ALL DIMENSIONS ARE IN mm WITH CONVERSION FOR (INCHES).

2) THE INTERFACE PROVIDED FOR MOUNTING THE ACTUATOR ON TO THE VALVE SHOULD CONFORM TO GOOD ENGINEERING PRACTICES, ENSURING ADEQUATE TOLERANCES, THREAD ENGAGEMENT, SCREW TORQUES, SIZES, MATERIALS & FORM TOLERANCES.

3) DIMENSIONS WITH " * " INDICATE COVER REMOVAL ALLOWANCE

UNIT WEIGHT -82 lbs (37.0 kg)

		<p>TOLERANCES DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE SPECIFIED X = ±.5mm XX = ±.1mm ANGULAR ±1°</p>			<p>rotork Controls MILWAUKEE, WISCONSIN, USA</p>		<p>TITLE: CMA INSTALLATION DRAWING</p>	
		SCALE:	PROJ. DIV:	PROJ. ENG.:	<p>FDR: CML1500 CML3000</p>			
1	INITIAL DESIGN	ECE 23FEB18	ECE		<p>This print is the property of Rotork Process Controls and is loaned in confidence subject to return. All rights to design or invention are reserved.</p>			
REV	DESCRIPTION	DATE	DATE	DATE	<p>PART NUMBER: 96D-049130-001</p>		REV: A	Sheet No. 1 of 1