


** Maximum available dimensions acc iso 5211

DESCRIPTION
 Travel : -5° to 95° adjustment
 Ratio : 40 : 1
 Turns to Close : 10
 Weight : 0.8 Kg (1.8 Lb) Excl Handwheel

MOUNTINGHOLES
 Bolt Circle : Min. Ø 42 [1.65] | Max. Ø 70 [4.92]
 (Off Center)
 Acc. ISO 5211 : F04 / F07 - F05 / F07
 Bore : Min. Ø8.4 [0.33] - Max. Ø15 [0.59]

TORQUE
 Max. Output : 125 Nm (100 lbf. in.)
 Max. Input : 12.5 Nm (10 lbf. in.)
 M.A. : 10 ± 10%



rotork-gears

Nijverheidstraat, 25
 7581 PV Loosdrecht
 The Netherlands

Gearbox 232-05 F04-F07 / F05-F07

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGMENT OF THE FOREGOING CONDITIONS.

Drawn : N.M

Date : 09-02-07

Dwg. Nr.: D232-05

Rev.: 00

Contents Subject to change without notice.