


** Maximum available dimensions acc iso 5211

DESCRIPTION	
Travel	: -5° to 95° adjustment
Ratio	: 40 : 1
Turns to Close	: 10
Weight	: 0.9 Kg. (2.0 Lb) Excl. Handwheel

MOUNTINGHOLES	
Bolt Circle	: Min. Ø 50 [1.97] Max. Ø 70 [2.75]
(Off Center)	
Acc. ISO 5211	: F05 - F07
Bore	: Min. Ø8.4 [0.33] Max. Ø20 [0.79]

TORQUE	
Max. Output	250 Nm [2200 lbf. in.]
Max. Input	25 Nm [220 lbf. in.]
M.A.	: 10 ± 10%



rotork-gears

Nijverheidsstraat 25
7581 PV Loosdrecht
The Netherlands

Gearbox 232-06 F05 / F07 (prep. for insert)

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS

Drawn : N.M

Date : 09-02-07

Dwg. Nr.: D232-06

Rev.: 00

Contents Subject to change without notice.