

**DESCRIPTION**


TRAVEL : 90° ±5° AT BOTH ENDS.  
 RATIO : 37 : 1  
 TURNS TO CLOSE : 9,25  
 WEIGHT : 2.5 kg. excl.handwheel

**MOUNTING DIMENSIONS**

BOLT CIRCLE : min.  $\phi 50 [1.79]$   
 (OFF CENTER) : max.  $\phi 70 [2.76]$   
 acc. ISO 5211 : F05 - F07  
 BORE : min. 8.4 [0.33] max.  $\phi 20 [0.79]$  #17

**TORQUE**

max. OUTPUT : 250 Nm (2200 lbf.in.)  
 max. INPUT : 21 Nm (182 lbf.in.)  
 M.A. : 11,9 ±10%




**rotork-gears**

Nijverheidstraat 25  
 7521 NJ Loosdrecht  
 The Netherlands

# GEARBOX E 232-07 LX

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : JK  
 Dwg Nf.: D50L-001  
 Date : 11-12-2001  
 Rev.: 01