


** Maximum available dimensions acc iso 5211

Max STEM height
58.5 [2.30]

DESCRIPTION	
Travel	: -5° to 95° adjustment
Ratio	: 37:1
Turns to Close	: 9.25
Weight	: 1.55 Kg, 6.43 Lb) Excl Handwheel

MOUNTINGHOLES	
Bolt Circle	: Min. Ø 70 [2.76] (Off Center) Max. Ø 102 [4.02] Acc. ISO 5211 : F07 - F10
Bore	: Min. Ø16 [0.63] - Max. Ø30 [1.18]

TORQUE	
Max. Output	500 Nm [400 lbf. in.)
Max. Input	41.7 Nm [662 lbf. in.)
M.A.	: 12 ±10%



rotork-gears

Nijverheidsstraat 25
7581 PV Loosdrecht
The Netherlands

Gearbox 232-08 F07 / F10 (prep. for insert)

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS

Drawn : N.M

Date : 09-02-07

Dwg. Nr.: D232-08

Rev.: 00

Contents Subject to change without notice.