

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 45 : 1
 TURNS TO CLOSE : 11,25
 WEIGHT : 3,5 kg (7,7 lb) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. \varnothing 70 [2.76]
 (OFF CENTER) max. \varnothing 125 [4.92]
 acc. ISO 5211 : F07-F10-F12
 BORE : min.16[0.63]max. \varnothing 30[1.18]#24

TORQUE

max.OUTPUT : 500 Nm (4400 lbf.in.)
 max.INPUT : 39 Nm (338 lbf.in.)
 M.A. : 12,8 ±10%




rotork-gears

Nijverheidsweg 25
 7581 NV Lasser
 The Netherlands

GEARBOX 232-10 LX

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS, NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DERIVATIVE TO THE INTEREST OF ROTORK GEARS, ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : JK
 Dwg Nr.: D51L-001

Date : NOV. 2001
 Rev.: 01