


** Maximum available dimensions acc iso 5211

| DESCRIPTION | |
|----------------|-----------------------------------|
| Travel | : -5° to 95° adjustment |
| Ratio | : 45:1 |
| Turns to Close | : 11.25 |
| Weight | : 2.9 Kg (6.3 Lb) Excl. Handwheel |

| MOUNTINGHOLES | |
|---------------|--------------------------------------------------------------------|
| Bolt Circle | : Min. Ø 102 [4.02] Max. Ø 125 [4.92] Acc. ISO 5211: F10 - F12 |
| Bore | : Min. Ø161[0.63] - Max. Ø141[1.73] |

| TORQUE | |
|-------------|----------------------|
| Max. Output | 900 Nm [920 lbf.in.] |
| Max. Input | 75 Nm [660 lbf.in.] |
| M.A. | : 12 ±10% |



rotork-gears

Nijverheidstraat 25
7581 PV Loosdrecht
The Netherlands

Gearbox 232-11 F10/F12 (prep. for insert)

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE REPRODUCED OR USED IN ANY OTHER WAY. PERMISSION TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS.

Drawn : N.M

Date : 09-02-07

Dwg. Nr.: D232-11

Rev.: 00

Contents Subject to change without notice.