


DESCRIPTION	
Travel	: -5° to 95° adjustment
Ratio	: 40 : 1
Turns to Close	: 10
Weight	: 5.4 Kg (11.9 Lb) Excl. Handwheel

MOUNTINGHOLES	
Bolt Circle	: Per Application
Bore	: Max. G55 [1.77] Key 16 [0.63]
	: Max. DD 46 [1.81] x 52 [2.05]
	: Max. SQ 46 [1.81]

TORQUE	
Max. Output	1500 Nm (13200 lbf in.)
Max. Input	125 Nm (1100 lbf in.)
M.A.	: 12 ± 10%



rotork-gears

Nijverheidstraat 25
7581 PV Loosdrecht
The Netherlands

Gearbox 232-15

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS.



Drawn : N.M

Date : 09-02-07

Dwg. Nr.: D232-15

Rev.: 00

Contents Subject to change without notice.