


Suitable for 150 series insert

DESCRIPTION	
TRAVEL	: -5° to 95° adjustable
RATIO	: 55 : 1
TURNS TO CLOSE	: 13.75
WEIGHT	: 22 kg. (48 lb) excl. handwheel

MOUNTINGHOLES	
BOLT CIRCLE (OFF CENTER)	: min. $\phi 102$ [4.02] max. $\phi 165$ [6.50]
acc. ISO 5211	: F10-F12-F14-F16
BORE	: min. $\phi 16$ [0.63] max. $\phi 44$ [1.77] #36 [1.42]

TORQUE	
max. OUTPUT	: 3250 Nm (28675 lbf.in.)
max. INPUT	: 171 Nm (1514 lbf.in.)
M.A.	: 19 ±15%




Dimensions in MM [inch]

**rotork gears**

Nijenheidestraat 25  
7581 PV Losser  
The Netherlands

# GEARBOX AB 1250 G

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE AVOIDANCE OF THE PERSONS' CONDITIONS



Drawn : N.M

Date : 20-06-06

Dwg Nr.: D05G1-001

Rev.: 01