


Suitable for 150 series insert

DESCRIPTION
 TRAVEL : -5° to 95° adjustable
 RATIO : 55 : 1
 TURNS TO CLOSE : 13.75
 WEIGHT : 27.5kg. (60.6lb) excl.handwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. $\phi 102$ [4.02]
 (OFF CENTER) max. $\phi 254$ [10]
 acc. ISO 5211 : F10/12/14/16/25
 BORE : min. $\phi 16$ [0.63] max. $\phi 44$ [1.77] #36[1.42]

TORQUE
 max.OUTPUT : 3250 Nm (28675 lbf.in.)
 max.INPUT : 171 Nm (1514 lbf.in.)
 M.A. : 19 \pm 15%




Dimensions in MM [inch]

rotork gears

Nijenheidestraat 25
 7581 PV Losser
 The Netherlands

GEARBOX AB 1250 G LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED BY THE INTERESTS OF ROTORK GEARS. ANY PART OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLEMENT OF THE FOREGOING CONDITIONS



Drawn : S.B.
 Date : 06-11-2009
 Dwg Nr.: D05G1 LB-001
 Rev.: 01

Contents Subject to change without notice.