

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 55 : 1
 TURNS TO CLOSE : 13.75
 WEIGHT : 22kg. (48.5lb) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 102$ [4.02]
 (OFF CENTER) max. $\phi 165$ [6.50]
 acc. ISO 5211 : F10-F12-F14-F16
 BORE : min.20[0.79] max.65[2.56] #50[1.97]

TORQUE

max.OUTPUT : 3250 Nm (28765 lbf.in.)
 max.INPUT : 171 Nm (1514 lbf.in.)
 M.A. : 19 ±15%



Dimensions in MM [inch]

rotork gears

Nijenheidestraat 25
 7581 PV Loosdrecht
 The Netherlands

GEARBOX AB 1250 W

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN CONSENT OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A BREACH OF THE PATENT RIGHTS AND CONDITIONS



Drawn : J.H.

Date : 15-03-02

Dwg Nr.: D05W-001

Rev.: 05