

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 55 : 1
 TURNS TO CLOSE : 13.75
 WEIGHT : 27.5kg.(60.6lb) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. ϕ 102 [4.02]
 (OFF CENTER) max. ϕ 254 [10]
 acc. ISO 5211 : F10/12/14/16/25
 BORE : min.20[0.79] max. ϕ 65[2.56] #50[1.97]

TORQUE

max.OUTPUT : 3250 Nm (28765 lbf.in.)
 max.INPUT : 171 Nm (1514 lbf.in.)
 M.A. : 19 ±15%




rotork gears

Nijenheldestraat 25
 72581 PV Losser
 The Netherlands

GEARBOX AB 1250 W LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ABOVE FINDE OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEMENT OF THE FOREGOING CONVENTIONS



Drawn : S.B.

Date : 06-11-2009

Dwg Nr.: D05WLB-001

Rev.: 01