

**DESCRIPTION**


TRAVEL : -5° TO 95° adjustable  
 RATIO : 52 : 1  
 TURNS TO CLOSE : 13  
 WEIGHT : 32,5kg.(72 Lb) excl.handwheel

**MOUNTINGHOLES**

BOLT CIRCLE : min.  $\phi$ 125 [4.92]  
 (OFF CENTER) max.  $\phi$ 254 [10.00]  
 acc. ISO 5211 : F12-F14-F16-F25  
 BORE : min.30[1.18] max.80[3.15] #60[2.36]

**TORQUE**

max.OUTPUT : 5500 Nm (48679 lbf.in.)  
 max.INPUT : 289 Nm (2562 lbf.in.)  
 M.A. : 19 ±15%




Dimensions in MM [inch]

**rotork gears**  
 Nijverheidstroet 25  
 72581 PV Losser  
 The Netherlands

**GEARBOX AB 1950 CS**

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ANYONE WHOSE NAME OF THIS DOCUMENT SHALL CONSULT THE KNOWLEDGEABLEMENT OF THE FOREGOING CONDITIONS



Drawn : B.H  
 Dwg Nr.: D06CS-001  
 Date : 18-07-2011  
 Rev.: 00