

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 52 : 1
 TURNS TO CLOSE : 13
 WEIGHT : 32kg.(70.5Lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. ϕ 125 [4.92]
 (OFF CENTER) max. ϕ 254 [10.00]
 acc. ISO 5211 : F12-F14-F16-F25
 BORE : min.30[1.18] max.80[3.15] #60[2.36]

TORQUE

max.OUTPUT : 5500 Nm (48679 lbf.in.)
 max.INPUT : 289 Nm (2562 lbf.in.)
 M.A. : 19 ±15%




rotork gears

Nijenheidestraat 25
 72581 PV Losser
 The Netherlands

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY OR FOR ANY OTHER PURPOSE WITHOUT THE WRITTEN PERMISSION OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A BREACH OF THE PATENT RIGHTS OF ROTORK GEARS.

GEARBOX AB 1950 W



Drawn : J.H

Date : 21-03-02

Dwg Nr.: D06W-001

Rev.: 06