


Suitable for insert 240 serie

DESCRIPTION	
TRAVEL	: 90° ±5° AT BOTH ENDS.
RATIO	: 52 : 1
TURNS TO CLOSE	: 13
WEIGHT	: 32kg.(70.5lb.) excl.handwheel

MOUNTINGHOLES	
BOLT CIRCLE (OFF CENTER)	: min. ϕ 125 [4.92] max. ϕ 254 [10.00]
acc. ISO 5211	: F12-F14-F16-F25
BORE	: min.16[0.63] max. ϕ 55[2.05] #46[1.81]

TORQUE	
max.OUTPUT	: 5500 Nm (48679 lbf.in.)
max.INPUT	: 289 Nm (2562 lbf.in.)
M.A.	: 19 ±15%




rotork gears

Nijenheidestraat 25
7581 PV Losser
The Netherlands

GEARBOX AB 1950 W

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ABOVE PHASE OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGE AND THE FOREGOING CONDITIONS



Drawn : N.M

Date : 22-06-06

Dwg Nr.: D06W1-001

Rev.: 01