


Suitable for insert 240 serie

DESCRIPTION
 TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 52 : 1
 TURNS TO CLOSE : 13
 WEIGHT : 44.7kg.(98.5lb.)\excl.handwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. $\phi 125$ [4.92]
 (OFF CENTER) max. $\phi 298$ [11.73]
 acc. ISO 5211 : F12-F14-F16-F25-F30
 BORE : min.16[0.63] max. $\phi 55$ [2.05] #46[1.81]

TORQUE
 max.OUTPUT : 5500 Nm (48679 lbf.in.)
 max.INPUT : 289 Nm (2562 lbf.in.)
 M.A. : 19 ±15%




rotork gears

Nijenheidestraat 25
 72581 PV Losser
 The Netherlands

GEARBOX AB 1950W LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED BY THE INTERESTS OF ROTORK GEARS. ANY PART OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLEMENT OF THE PATENT RIGHTS CONSIDERED.



Drawn : N.M

Date : 08-12-08

Dwg Nr.: D06WILB-001

Rev.: 01