


Suitable for insert 07 serie

DESCRIPTION
 TRAVEL : -5° to 95° adjustable
 RATIO : 37 : 1
 TURNS TO CLOSE : 9.25
 WEIGHT : 3.5 kg. (7.7 Lb.) excl.handwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. $\varnothing 50$ [1.97]
 (OFF CENTER) max. $\varnothing 102$ [4.02]
 acc. ISO 5211 : F05-F07-F10
 BORE : min.8.4[0.33] max. $\varnothing 20$ [0.79] #17[0.67]

TORQUE
 max.OUTPUT : 330 Nm (2921 lbf.in.)
 max.INPUT : 28.5 Nm (252 lbf.in.)
 M.A. : 11.6 ± 15%




Dimensions in MM [inch]

rotork gears

Nijenheidestraat 25
 72581 PV Losser
 The Netherlands

GEARBOX AB 210 G

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED. TO THE INTEREST OF ROTORK GEARS, ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLEMENT OF THE PREVIOUS CONDITIONS



Drawn : N.M

Date : 22-06-06

Dwg Nr.: D02G1-001

Rev.: 02