


Suitable for insert 07 serie

DESCRIPTION
 TRAVEL : -5° to 95° adjustable
 RATIO : 37 : 1
 TURNS TO CLOSE : 9.25
 WEIGHT : 5.5 kg. (12.1lb) excl.handwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. $\phi 50$ [1.97]
 (OFF CENTER) max. $\phi 125$ [4.92]
 acc. ISO 5211 : F05-F07-F10-F12
 BORE : min.8.4[0.33] max. $\phi 20$ [0.79] #17[0.67]

TORQUE
 max.OUTPUT : 330 Nm (2921 lbf.in.)
 max.INPUT : 28.5 Nm (252 lbf.in.)
 M.A. : 11.6 ±15%




Dimensions in MM [inch]

rotork gears

Nijverheidstroet 25
 7581 PV Loosdrecht
 The Netherlands

GEARBOX AB 210 N LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN PERMISSION OF ROTORK GEARS. ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLEMENT OF THE FOREGOING CONDITIONS



Drawn : S.B.

Dwg Nr.: D02NI LB-001

Date : 05-11-2009

Rev.: 01