

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 37 : 1
 TURNS TO CLOSE : 9.25
 WEIGHT : 3.5 kg. (7.7 Lb) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 50 [1.97]$
 (OFF CENTER) max. $\phi 102 [4.02]$
 acc. ISO 5211 : F05-F07-F10
 BORE : min. $10.4[0.41]$ max. $\phi 30[1.18]$ #24[0.94]

TORQUE

max.OUTPUT : 330 Nm (2921 lbf.in.)
 max.INPUT : 28.5 Nm (252 lbf.in.)
 M.A. : 11.6 ±15%




rotork gears

Nijenheidestraat 25
 7581 PV Loosdrecht
 The Netherlands

GEARBOX AB 210 W

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN PERMISSION OF ROTORK GEARS. ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE ADOPTION/RENDERMENT OF THE FOREGOING CONDITIONS



Drawn : J.H
 Dwg Nr.: D02W-001

Date : 07-03-02
 Rev.: 09