


Max. STEM height
54 [2.13]

DESCRIPTION
 TRAVEL : -5° to 95° adjustable
 RATIO : 37 : 1
 TURNS TO CLOSE : 9.25
 WEIGHT : 5.5 kg. (12.1 Lb)
 acc: handwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. $\phi 50$ [1.97]
 (OFF CENTER) max. $\phi 125$ [4.92]
 acc. ISO 5211 : F05-F07-F10-F12
 BORE : min. $\phi 10.4$ [0.41] max. $\phi 30$ [1.18] #24 [0.94]

TORQUE
 max. OUTPUT : 330 Nm (2921 lbf.in.)
 max. INPUT : 28.5 Nm (252 lbf.in.)
 M.A. : 11.6 $\pm 15\%$




rotork gears

Nijverheidstroet 25
 7281 PV Losser
 The Netherlands

GEARBOX AB 210 W LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ANY PART OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGE OF THE FOREGOING CONDITIONS



Drawn : S.B.

Date : 04-11-2009

Dwg Nr.: D02WLB-001

Rev.: 01