

Max. STEM height
54 [2.13]

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 37 : 1
 TURNS TO CLOSE : 9.25
 WEIGHT : 4 kg. (8.8 Lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 50$ [1.97]
 (OFF CENTER) max. $\phi 102$ [4.02]
 acc. ISO 5211 : F05-F07-F10
 BORE : min.10.4[0.41] max. $\phi 30$ [1.18] #24[0.94]

TORQUE

max.OUTPUT : 500 Nm (4425 lbf.in.)
 max.INPUT : 43 Nm (381 lbf.in.)
 M.A. : 11.6 $\pm 15\%$




Dimensions in MM [inch]

rotork gears

Nijverheidstroet 25
 72581 PV Losser
 The Netherlands

GEARBOX AB 215G BUL

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN PERMISSION OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLE VIOLATION OF THE PATENT RIGHTS OF ROTORK GEARS.



Drawn : P.VH

Date : 28-01-09

Dwg Nr.: AB 215G BUL

Rev.: 01