

Suitable for insert 07 serie

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 37 : 1
 TURNS TO CLOSE : 9.25
 WEIGHT : 4 kg. (8.8 Lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 50$ [1.97]
 (OFF CENTER) max. $\phi 102$ [4.02]
 acc. ISO 5211 : F05-F07-F10
 BORE : min.8.4[0.33] max. $\phi 20$ [0.79] #17[0.67]

TORQUE

max.OUTPUT : 500 Nm (4425 lbf.in.)
 max.INPUT : 43 Nm (381 lbf.in.)
 M.A. : 11.6 ±15%




rotork gears

Nijenheidestraat 25
 7581 PV Losser
 The Netherlands

GEARBOX AB 215 G

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ABOVE FRAME OF THIS DOCUMENT SHALL CONSTITUTE KNOWLEDGEMENT OF THE PERSONS IN POSSESSION



Drawn : N.M Date : 22-06-06
 Dwg.Nr.: D02GI-011 Rev.: 02