

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 37 : 1
 TURNS TO CLOSE : 9.25
 WEIGHT : 5.5 kg. (12.1lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 50$ [1.97]
 (OFF CENTER) max. $\phi 125$ [4.92]
 acc. ISO 5211 : F05-F07-F10-F12
 BORE : min.10.4[0.41] max. $\phi 30$ [1.18] #24[0.94]

TORQUE

max.OUTPUT : 500 Nm (4425 lbf.in.)
 max.INPUT : 43 Nm (381 lbf.in.)
 M.A. : 11.6 ±15%




rotork gears

Nijverheidstroet 25
 72581 PV Losser
 The Netherlands

GEARBOX AB 215G BU LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE INTEREST OF ROTORK GEARS. ABOVE FINDE OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : S.B.

Date : 05-11-2009

Dwg Nr.: AB 215G LB BU L

Rev.: 01