

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 37 : 1
 TURNS TO CLOSE : 9.25
 WEIGHT : 5.5 kg. (12.1lb) excl. handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\varnothing 50$ [1.97]
 (OFF CENTER) max. $\varnothing 125$ [4.92]
 acc. ISO 5211 : F05-F07-F10-F12
 BORE : min. 10.4 [0.41] max. $\varnothing 50$ [1.98] #24 [0.94]

TORQUE

max. OUTPUT : 500 Nm (4425 lbf.in.)
 max. INPUT : 43 Nm (381 lbf.in.)
 M.A. : 11.6 ±15%




Dimensions in MM [inch]

rotork gears
 Nijverheidstroet 25
 7281 PV Losser
 The Netherlands

GEARBOX AB 215 W LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ANY PART OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGE ELEMENT OF THE PERSONS CONVICTIONS



Drawn : S.B. Date : 04-11-2009
 Dwg Nr.: D02WLB-011 Rev.: 01