


Suitable for insert 10 serie

DESCRIPTION
 TRAVEL : -5° to 95° adjustable
 RATIO : 34 : 1
 TURNS TO CLOSE : 8,5
 WEIGHT : 8,5 kg.(18.7lb) exchhandwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. $\phi 70 [2.76]$
 (OFF CENTER) max. $\phi 140 [5.51]$
 acc. ISO 5211 : F07-F10-F12-F14
 BORE : min. $\phi 16 [0.63]$ max. $\phi 30 [1.18]$ #27 [1.06]

TORQUE
 max.OUTPUT : 1000 Nm (8851 lbf.in.)
 max.INPUT : 83 Nm (738 lbf.in.)
 M.A. : 12.0 ±15%




rotork gears

Nijenheidestraat 25
 7581 PV Loosdrecht
 The Netherlands

GEARBOX AB 550G

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ASSESS VALUE OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGELEMENT OF THE PERSONS IN POSSESSION.



Drawn : N.M

Date : 22-06-06

Dwg Nr.: D03G1-01

Rev.: 01