


Suitable for insert 10 serie

DESCRIPTION
 TRAVEL : -5° to 95° adjustable
 RATIO : 34 : 1
 TURNS TO CLOSE : 8,5
 WEIGHT : 11,5 kg.(25.3lb) excl.handwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. $\phi 70 [2.76]$
 (OFF CENTER) max. $\phi 165 [6.50]$
 acc. ISO 5211 : F07-F10-F12-F14-F16
 BORE : min. $\phi 16 [0.63]$ max. $\phi 30 [1.18]$ #27 [1.06]

TORQUE
 max.OUTPUT : 1000 Nm (8851 lbf.in.)
 max.INPUT : 83 Nm (738 lbf.in.)
 M.A. : 12.0 ± 15%




Dimensions in MM [inch]

rotork gears

Nijverheidstroet 25
 7581 PV Losser
 The Netherlands

GEARBOX AB 550G LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED BY THE INTERNS OF ROTORK GEARS. ABOVE FINDE OF THIS DOCUMENT SHALL CONSTITUTE A FORMAL REPRISAL OF THE PERSONS CONVICTIONS



Drawn : N.M.

Date : 10-03-2010

Dwg Nr.: D03GILB-001

Rev.: 01