


DESCRIPTION
 TRAVEL : -5 TO 95° adjustable
 RATIO : 34 : 1
 TURNS TO CLOSE : 8.5
 WEIGHT : 8,5 kg.(18.7Lb) excl.handwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. $\phi 70$ [2.76]
 (OFF CENTER) max. $\phi 140$ [5.51]
 acc. ISO 5211 : F07-F10-F12-F14
 BORE : min.16[0.63] max. $\phi 45$ [1.77] #38[1.50]

TORQUE
 max.OUTPUT : 1000 Nm (8851 lbf.in.)
 max.INPUT : 83 Nm (738 lbf.in.)
 M.A. : 12.0 \pm 15%




rotork gears

Nijenheidestraat 25
 72581 PV Losser
 The Netherlands

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED BY THE INTERESTS OF ROTORK GEARS. ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEMENT OF THE APPLICABLE CONDITIONS

GEARBOX AB 550N



Drawn : H.L
 Date : Jan. 2000
 Dwg Nr.: D03N-001
 Rev.: 03