


DESCRIPTION
 TRAVEL : -5 TO 95° adjustable
 RATIO : 34 : 1
 TURNS TO CLOSE : 8.5
 WEIGHT : 11,5 kg.(25.3Lb) excl.handwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. $\phi 70 [2.76]$
 (OFF CENTER) max. $\phi 165 [6.50]$
 acc. ISO 5211 : F07-F10-F12-F14-F16
 BORE : min. $\phi 10.63 [0.415]$ max. $\phi 45 [1.77]$ #38 [1.50]

TORQUE
 max.OUTPUT : 1000 Nm (8851 lbf.in.)
 max.INPUT : 83 Nm (738 lbf.in.)
 M.A. : 12.0 \pm 15%



Dimensions in MM [inch]

rotork gears

Nijenheidestraat 25
 72581 PV Losser
 The Netherlands

GEARBOX AB 550N LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ANY PART OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGE OF THE PERSONS CONDITIONS



Drawn : N.M.
 Dwg Nr.: D03NLB-001

Date : 10-03-2010
 Rev.: 02