


Suitable for insert 10 serie

DESCRIPTION
 TRAVEL : -5° to 95° adjustable
 RATIO : 34 : 1
 TURNS TO CLOSE : 8,5
 WEIGHT : 11,5 kg.(25.3lb) excl.handwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. \varnothing 70 [2.76]
 (OFF CENTER) max. \varnothing 165 [6.50]
 acc. ISO 5211 : F07-F10-F12-F14-F16
 BORE : min.16[0.63] max. \varnothing 30[1.18]#27[1.06]

TORQUE
 max.OUTPUT : 1000 Nm (8851 lbf.in.)
 max.INPUT : 83 Nm (738 lbf.in.)
 M.A. : 12.0 \pm 15%




rotork gears

Nijverheidstroet 25
 7581 PV Loosdrecht
 The Netherlands

GEARBOX AB 550W LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN PERMISSION OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A VIOLATION OF THE PATENT RIGHTS AND CONDITIONS OF THE PATENT RIGHTS.



Drawn : N.M
 Date : 10-03-2010
 Dwg Nr.: D03WILB-001
 Rev.: 02