

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 78 : 1
 TURNS TO CLOSE : 19,5
 WEIGHT : 56,5kg.(125Lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. ϕ 165 [6.50]
 (OFF CENTER) max. ϕ 298 [11.73]
 acc. ISO 5211 : F16-F25-F30
 BORE : min. ϕ 130[5.12] max. ϕ 100[3.94] #75[2.95]

TORQUE

max.OUTPUT : 8400 Nm (74364 lbf.in.)
 max.INPUT : 305 Nm (2704 lbf.in.)
 M.A. : 27,5 ±15%



rotork gears

Nijenheidestraat 25
 72581 PV Losser
 The Netherlands

GEARBOX AB 6800 G

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY. PERMISSION TO REPRODUCE OR TRANSMIT IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT PERMISSION IN WRITING FROM ROTORK GEARS, IS PROHIBITED.



Drawn : H.L.
 Dwg Nr.: D08G-001

Date : JAN. 2000
 Rev.: 05