

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 78 : 1
 TURNS TO CLOSE : 19,5
 WEIGHT : 86,9kg.(192Lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 165$ [6.50]
 (OFF CENTER) max. $\phi 356$ [14.02]
 acc. ISO 5211 : F16-F25-F30-F35
 BORE : min. $\phi 100$ [3.94] max. $\phi 100$ [3.94] #75[2.95]

TORQUE

max.OUTPUT : 8400 Nm (74364 lbf.in.)
 max.INPUT : 305 Nm (2704 lbf.in.)
 M.A. : 27,5 ±15%




Dimensions in MM [inch]

rotork gears

Nijverheidstroet 25
 72581 PV Losser
 The Netherlands

GEARBOX AB 6800G BU LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY. RETURN TO THE INTEREST OF ROTORK GEARS. ANY CHANGE OF THIS DOCUMENT SHALL CONSTITUTE A SIGNIFICANT DEVIATION OF THE ORIGINAL CONDITIONS.



Drawn : P.VH
 Date : 28-01-09
 Dwg Nr.: AB 6800G BU LB
 Rev.: 01