

**DESCRIPTION**


TRAVEL : 90° ±5° AT BOTH ENDS.  
 RATIO : 78 : 1  
 TURNS TO CLOSE : 19,5  
 WEIGHT : 56,5kg.(125Lb.) excl.handwheel

**MOUNTINGHOLES**

BOLT CIRCLE : min.  $\phi 165$  [6.50]  
 (OFF CENTER) : max.  $\phi 298$  [11.73]  
 acc. ISO 5211 : F16-F25-F30  
 BORE : min. $\phi 30$ [1.18] max. $\phi 100$ [3.94] #75[2.95]

**TORQUE**

max.OUTPUT : 8400 Nm (74364 lbf.in.)  
 max.INPUT : 305 Nm (2704 lbf.in.)  
 M.A. : 27,5 ±15%




**rotork gears**

Nijverheidstraat 25  
 7581 PV Loosdrecht  
 The Netherlands

**GEARBOX AB 6800G BUL**

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY. PERMISSION TO REPRODUCE OR TRANSMIT IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT PERMISSION IN WRITING FROM ROTORK GEARS, IS PROHIBITED.



Drawn : P.VH  
 Date : 28-01-09  
 Dwg Nr.: AB 6800G BUL  
 Rev.: 01