

**DESCRIPTION**


TRAVEL : 90° ±5° AT BOTH ENDS.  
 RATIO : 78 : 1  
 TURNS TO CLOSE : 19,5  
 WEIGHT : 56kg.(123lb.) excl.handwheel

**MOUNTINGHOLES**

BOLT CIRCLE : min.  $\phi$ 165 [6.50]  
 (OFF CENTER) max.  $\phi$ 298 [11.73]  
 acc. ISO 5211 : F16-F25-F30  
 BORE : min.30[1.18]max. $\phi$ 100[3.94] #75[2.95]

**TORQUE**

max.OUTPUT : 8400 Nm (74346 lbf.in.)  
 max.INPUT : 305 Nm (2704 lbf.in.)  
 M.A. : 27,5 ±15%




Dimensions in MM [inch]

**rotork gears**

Nijenheidestraat 25  
 72581 PV Losser  
 The Netherlands

# GEARBOX AB 6800 N

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE EXPRESS WRITTEN PERMISSION OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A BREACH OF THE ABOVE MENTIONED CONDITIONS.



Drawn : H.L

Dwg Nr.: D08N-001

Date : JAN. 2000

Rev.: 04