

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 78 : 1
 TURNS TO CLOSE : 19,5
 WEIGHT : 86.9kg.(192Lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. ϕ 165 [6.50]
 (OFF CENTER) max. ϕ 356 [14.02]
 acc. ISO 5211 : F16-F25-F30-F35
 BORE : min.30[1.18]max. ϕ 100[3.94] #75[2.95]

TORQUE

max.OUTPUT : 8400 Nm (74346 lbf.in.)
 max.INPUT : 305 Nm (2704 lbf.in.)
 M.A. : 27,5 ±15%




rotork gears

Nijenheidestraat 25
 7581 PV Loosdrecht
 The Netherlands

GEARBOX AB 6800N LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY. RETURN TO THE INTERESTS OF ROTORK GEARS. ASSESSOR OF THIS DOCUMENT SHALL CONSTITUTE A FORMAL AGREEMENT ON THE FOREGOING CONDITIONS



Drawn : N.M.

Date : 09-12-08

Dwg Nr.: D08N1LB-001

Rev.: 01