

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 78 : 1
 TURNS TO CLOSE : 19,5
 WEIGHT : 56 kg.(123 lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 165$ [6.50]
 (OFF CENTER) max. $\phi 298$ [11.73]
 ecc. ISO 5211 : F16-F25-F30
 BORE : min.30[1.18]max. $\phi 100$ [3.94] #75[2.95]

TORQUE

max.OUTPUT : 8400 Nm (74346 lbf.in.)
 max.INPUT : 305 Nm (2704 lbf.in.)
 M.A. : 27,5 ±15%




Dimensions in MM [inch]

rotork gears

Nijenheidestraat 25
 7581 PV Losser
 The Netherlands

GEARBOX AB 6800 W

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLEMENT OF THE FOREGOING CONDITIONS



Drawn : J.H

Date : 22-03-02

Dwg Nr.: D08W-001

Rev.: 06