

**DESCRIPTION**


Travel : -5° to 95° adjustment  
 Ratio : 38 : 1  
 Turns to Close : 9.5  
 Weight : 14 Kg. (31 Lb.) Excl. Handwheel

**MOUNTINGHOLES**

Bolt Circle : Min.  $\phi 102$  [4.02 ]  
 (Off Center) Max.  $\phi 165$  [6.5 ]  
 Acc. ISO 5211 : F10 - F12 - F14 - F16  
 Bore: Min.  $\phi 16$  [0.63] - Max.  $\phi 60$  [2.36] # 46 [1.81]

**TORQUE**


Max Output : 2000 Nm ( 1770 lbf. in.)  
 Max. Input : 152 Nm ( 134 lbf. in.)  
 M.A. : 13.2 ± 15%



Nijverheidsweg 25  
 7581 PV Loosdrecht  
 The Netherlands

# GEARBOX AB 880N

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS, NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTERESTS OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : J.H. Date : 13-03-2002  
 Dwg Nr.: D04N-001 Rev.: 07