

DESCRIPTION


Travel : -5° to 95° adjustment
 Ratio : 38 : 1
 Turns to Close : 9.5
 Weight : 14 Kg. (31 Lb.) Excl. Handwheel

MOUNTINGHOLES

Bolt Circle : Min. \varnothing 102 [4.02]
 (Off Center) Max. \varnothing 165 [6.5]
 Acc. ISO 5211 : F10 - F12 - F14 - F16
 Bore : Min. \varnothing 14 [0.63] - Max. \varnothing 44 [1.77] # 36[1.42]

TORQUE

Max Output : 2000 Nm (1770 lbf. in.)
 Max Input : 152 Nm (134 lbf. in.)
 M.A. : 13.2 ± 15%



Suitable for insert 150 serie


Max. STEM height
82 [3.23]



Nijverheidsweg 25
 7581 PV Loosdrecht
 The Netherlands

GEARBOX AB 880N

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS, NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTERESTS OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : N.M
 Dwg Nr.: D04NI-001
 Date : 22-06-06
 Rev.: 01

Contents Subject to change without notice.