

**DESCRIPTION**


Travel : -5° to 95° adjustment  
 Ratio : 38 : 1  
 Turns to Close : 9.5  
 Weight : 17 Kg. (37.5Lb) Excl. Handwheel

**MOUNTINGHOLES**

Bolt Circle : Min.  $\varnothing$ 102 [4.02 ]  
 (Off Center) Max.  $\varnothing$ 220 [8.66 ] 8x M16  
 Acc. ISO 5211 : F10 - F12 - F14 - F16  
 Bore: Min.  $\varnothing$ 16 [0.63] - Max.  $\varnothing$ 60 [2.36] # 46 [1.81]

**TORQUE**

Max Output : 2000 Nm ( 1770 lbf.in.)  
 Max Input : 152 Nm ( 134 lbf.in.)  
 M.A. : 13.2 ± 15%



Nijverheidstraat 25  
 7581 PV Loosdrecht  
 The Netherlands

# GEARBOX AB 880N LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS, NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : S.B. Date : 05-11-2009  
 Dwg Nr.: D04N1LB-001 Rev.: 01