

DESCRIPTION


Travel : -5° to 95° adjustment
 Ratio : 38 : 1
 Turns to Close : 9.5
 Weight : 17 Kg. (37.5Lb) Excl. Handwheel

MOUNTINGHOLES

Bolt Circle : Min. \varnothing 102 [4.02]
 (Off Center) Max. \varnothing 220 [8.66] 8x M16
 Acc. ISO 5211 : F10 - F12 - F14 - F16
 Bore : Min. \varnothing 141.0631 - Max. \varnothing 44 [1.771 # 36(1.42)

TORQUE

Max Output : 2000 Nm (17701 lbf. in.)
 Max. Input : 152 Nm (1341 lbf. in.)
 M.A. : 13.2 ± 15%



Suitable for insert 150 serie

Max. STEM height.

82 [3.23]

260 [10.24]
175 [6.89]

130 [5.11]

86 [3.39]

154 [6.06]

189 [7.44]

\varnothing 6 [0.24]

\varnothing 20 [0.79]

24 [0.94]

93 [3.66]

42.5 [1.67]

\varnothing 60 [2.36]
 \varnothing 75 [2.95]
 BC OFF CENTER
 256 [10.07]

8.5 [0.33]



Nijverheidsweg 25
 7581 PV Loosdrecht
 The Netherlands

GEARBOX AB 880N LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS, NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : S.B. Date : 05-11-2009
 Dwg Nr.: D04NILB-001 Rev.: 01