



- NOTES:**
- 1) MAX ALLOWABLE OPERATING PRESSURE (MAOP) = 10 BAR (150 PSIG)
 - 2) WARNING - SEE K-TORK INSTALLATION, OPERATION & MAINTENANCE MANUAL BEFORE MOUNTING, INSTALLING OR SERVICING.
 - 3) ACTUATOR SHOWN IN FULL CW POSITION, SCRIBE ON SHAFT SHOWS VANE LOCATION.
 - 4) WEIGHT 210.46 kg (464.00 LB.)
 - 5) RESTRICTED TRAVEL VERSIONS OPTIONAL.
 - 6) ACTUATOR MAY BE REMOVED FROM AUTOMATED VALVE WHILE GEAR REMAINS ATTACHED TO OPERATE THE VALVE OR DAMPER.
 - 7) GEARBOX MECHANICAL STOPS, ADJUSTABLE
 - 8) GEAR ENGAGEMENT LEVER
 - 9) DECLUTCH PULL - PIN

SIDE VIEW

OPTIONAL COUPLING, MILD STEEL

BROACHED TO FIT BOTTOM DRIVE SHAFT

SIDE VIEW

BOTTOM MOUNTING VIEW

K-TORK
ACTUATORS + CONTROLS

Texas - USA
www.rotork.com

This drawing is confidential and is the property of Rotork Dallas Inc. and must not be reproduced either wholly or partly. All rights in respect of patents, designs and copyrights are reserved. © 2015

Document type	DETAIL DRAWING	
	Dimensions in mm	
	Scale 1:1	
Created	S.DINESH	03-FEB-2015
Checked	S.SUDHIR	03-FEB-2015
Approved	K.PRICE	03-FEB-2015

Title			K-6-DA-HWMO - IMPERIAL AIR PORTS & MOUNTING HOLES		
Drawing Number			D000000236		
Sheet	1	of	1	Size	A3
Rev	0				