

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 55 : 1
 TURNS TO CLOSE : 13.75
 WEIGHT : 22 kg (48.5 lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. ϕ 102 [4.02]
 (OFF CENTER) max. ϕ 165 [6.50]
 acc. ISO 5211 : F10-F12-F14-F16
 BORE : min.20[0.79] max. ϕ 65[2.56] #50[1.97]

TORQUE

max.OUTPUT : 3250 Nm (28765 lbf.in.)
 max.INPUT : 171 Nm (1514 lbf.in.)
 M.A. : 19 ±15%



rotork gears

Nijverheidstraat 25
 The Netherlands

GEARBOX E 1250 G / F10

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : J.H Date : 11-03-02

Dwg Nr.: D20G-001 Rev.: 06

Contents Subject to change without notice.