

MOVING INDICATOR

NON MOVING INDICATOR

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 37 : 1
 TURNS TO CLOSE : 9.25
 WEIGHT : 4 kg.(8.8 lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. \varnothing 50 [1.97]
 (OFF CENTER) max. \varnothing 102 [4.02]
 acc. ISO 5211 : F05 - F07 - F10
 BORE : min.8.4[0.33] max.830[1.18] #24[0.94]

TORQUE

max.OUTPUT : 330 Nm (2921 lbf.in.)
 max.INPUT : 28.5 Nm (252 lbf.in.)
 M.A. : 11.6 ±15%



Dimensions in MM [inch]

rotork gears

Nijenhelderroot 25
 7581 PV Losser
 The Netherlands

GEARBOX E 210 CS F10 L

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : B.H
 Date : 20-07-2011
 Dwg Nr.: E 210CS F10 L
 Rev.: 00