


Suitable for insert 07 serie

DESCRIPTION	
TRAVEL	: 90° ±5° AT BOTH ENDS.
RATIO	: 37 : 1
TURNS TO CLOSE	: 9.25
WEIGHT	: 4 kg.(8.8 lb.) excl.handwheel

MOUNTINGHOLES	
BOLT CIRCLE (OFF CENTER)	: min. $\phi 50$ [1.97]
occ. ISO 5211	: max. $\phi 102$ [4.02]
BORE	: min. 8.4[0.33] max. $\phi 20$ [0.79] #17[0.67]

TORQUE	
max.OUTPUT	: 330 Nm (2921 lbf.in.)
max.INPUT	: 28.5 Nm (252 lbf.in.)
M.A.	: 11.6 ±15%



Dimensions in MM [inch]

rotork gears

Nijenheidestraat 25
7581 PV Loosdrecht
The Netherlands

GEARBOX E 210 G F10 BUL

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN PERMISSION OF ROTORK GEARS. ANYONE WHOSE NAME OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLEMENT OF THE FOREGOING CONDITIONS



Drawn : P.VH

Date : 28-01-09

Dwg Nr.: E 210 GI F10 BUL

Rev.: 01