

**DESCRIPTION**


TRAVEL : 90° ±5° AT BOTH ENDS.  
 RATIO : 37 : 1  
 TURNS TO CLOSE : 9.25  
 WEIGHT : 4 kg.(8.8 lb.) excl.handwheel

**MOUNTINGHOLES**

BOLT CIRCLE : min.  $\phi 50$  [1.97]  
 (OFF CENTER) max.  $\phi 102$  [4.02]  
 acc. ISO 5211 : F05 - F07 - F10  
 BORE : min.8.4[0.33] max. $\phi 30$ [1.18] #24[0.94]

**TORQUE**

max.OUTPUT : 500 Nm (4425 lbf.in.)  
 max.INPUT : 43 Nm (381 lbf.in.)  
 M.A. : 11.6 ±15%



Dimensions in MM [Inch]

**rotork gears**

Nijenheidestraat 25  
 72581 PV Losser  
 The Netherlands

**GEARBOX E 215 G / F10**

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN CONSENT OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A VIOLATION OF THE PATENT RIGHTS AND CONDITIONS OF ROTORK GEARS.

Drawn : H.H

Date : 15-01-04

Dwg Nr.: D15G-011

Rev.: 02