


MOVING INDICATOR

NON MOVING INDICATOR

DESCRIPTION
 TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 34 : 1
 TURNS TO CLOSE : 8,5
 WEIGHT : 11 kg.(24.3 lb.) excl.handwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. ϕ 70 [2.76]
 (OFF CENTER) max. ϕ 140 [5.51]
 acc. ISO 5211 : F07-F10-F12-F14
 BORE : min. 16[0.63] max. 45[1.77] #38[1.50]

TORQUE
 max.OUTPUT : 1000 Nm (8851 lbf.in.)
 max.INPUT : 83 Nm (738 lbf.in.)
 M.A. : 12.0 ±15%



Dimensions in MM [inch]

rotork gears

Nijenheidestraat 25
 72581 PV Losser
 The Netherlands

GEARBOX E 550 CS F10 L

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE EXPRESS WRITTEN CONSENT OF ROTORK GEARS. IN THE INTEREST OF ROTORK GEARS, ASSESSOR OF THIS DOCUMENT SHALL CONSTITUTE KNOWLEDGEMENT OF THE PERSONS CONCERNED.



Drawn : B.H

Date : 20-07-2011

Dwg Nr.: E 550CS F10 L

Rev.: 00