

Suitable for insert 10 serie

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 34 : 1
 TURNS TO CLOSE : 8,5
 WEIGHT : 11 kg.(24.3 lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 70$ [2.76]
 (OFF CENTER) max. $\phi 140$ [5.51]
 acc. ISO 5211 : F07-F10-F12-F14
 BORE : min.16[0.63] max.30[1.18] #27[1.06]

TORQUE

max.OUTPUT : 1000 Nm (8851 lbf.in.)
 max.INPUT : 83 Nm (738 lbf.in.)
 M.A. : 12.0 ±15%




rotork gears

Nijenheidestraat 25
 7581 PV Loosdrecht
 The Netherlands

GEARBOX E 550G / F10

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ABOVE FINISH OF THIS DOCUMENT SHALL CONSTITUTE A SIGNIFICANT DEVIATION OF THE PRESERVE CONDITIONS



Drawn : N.M

Date : 22-06-06

Dwg Nr.: D16G1-001

Rev.: 01