

**DESCRIPTION**


TRAVEL : -5° to 95° adjustable  
 RATIO : 38 : 1  
 TURNS TO CLOSE : 9,5  
 WEIGHT : 14 kg.(31 lb.) excl.handwheel

**MOUNTINGHOLES**

BOLT CIRCLE : min.  $\phi$ 102 [4.02]  
 (OFF CENTER) max.  $\phi$ 165 [6.50]  
 acc. ISO 5211 : F10-F12-F14-F16  
 BORE : min.16[0.63] max. $\phi$ 60[2.36] #46[1.81]

**TORQUE**

max.OUTPUT : 2000 Nm (17701 lbf.in.)  
 max.INPUT : 152 Nm (1341 lbf.in.)  
 M.A. : 13.2  $\pm$ 15%




Dimensions in MM [inch]

**rotork gears**

Nijenheldestraat 25  
 72581 PV Losser  
 The Netherlands

**GEARBOX E 880G / F10**

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE EXPRESS WRITTEN PERMISSION OF ROTORK GEARS. ANY PERSON WHOSE NAME OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLEMENT OF THE FOREGOING CONDITIONS



Drawn : J.H

Date : 14-03-02

Dwg Nr.: D18G-001

Rev.: 06