



RATIO	M.A.	C.O.G.			MAX. OUTPUT TORQUE Nm (lbs-ft)
		X	Y	Z	
4	3.40	0	63	31	4067 (3000)
6	5.10	0	63	27	4067 (3000)

MAX BORE SQ KEY			MAX BORE RECTANGULAR KEY			MAX STEM SCREW ACCEPTANCE DIA.
STD	BORE	KEY	STD	BORE	KEY	
BS4235	-	-	BS4235	76.0	22x14	86(3.375")
BS46	2.750"	3/4" SQ	BS46	3.000"	3/4"x1/2"	
ANSI B17.1	2.750"	5/8" SQ	ANSI B17.1	3.000"	3/4"x1/2"	

	INPUT FLANGE DETAILS				
	FLANGE O/DIA. & THICKNESS	SHAFT DIA.	RECESS DIA.	RECESS DEPTH	HOLE DETAILS 22.5°(OFF CENTRES)
ISO F25	Ø300 x 20	Ø50.00±0.05	Ø200.10±0.10	5	8 HOLES Ø16.5 (Ø0.65")
	(Ø11.81" x 0.79")	(Ø1.969"-0.002")	(Ø7.878"+0.004")	(0.20")	ON Ø254.0 (Ø10.00") P.C. (0.55"x0.35"x2.17")
FA25	Ø300 x 20	Ø50.00±0.05	Ø152.37±0.10	5	8 HOLES Ø16.5 (Ø0.65")
	(Ø11.81" x 0.79")	(Ø1.969"-0.002")	(Ø5.999"+0.004")	(0.20")	ON Ø254.0 (Ø10.00") P.C. (0.55"x0.35"x2.17")

	BASEPLATE DETAILS	
	SPIGOT DIA.	HOLE DETAILS (22.5° OFF CENTRES)
ISO F30	Ø229.95±0.05	8 HOLES M20x25 (0.98") DEEP (Ø9.053"-0.002")
	ON Ø298.0 (Ø11.73") P.C.	ON Ø298.0 (Ø11.73") P.C.
FA30	Ø177.70±0.05	8 HOLES 3/4"UNCx25 (0.98") DEEP (Ø6.996"-0.002")
	ON Ø298.5 (Ø11.75") P.C.	ON Ø298.5 (Ø11.75") P.C.

**rotork
gears**

**IB10 GEARBOX
F25/FA25 INPUT F30/FA30 OUTPUT**

DETAILS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

FOR UP TO DATE DETAILS VISIT www.rotork.com

APPROX WEIGHT 106.8 kg

DRAWING No	PUBIB10-F25-F30
ISSUE	01
DATE	10/05/2011

**Regina House
Ring Road
Bramley
Leeds
LS134ET
United Kingdom**