



8 OFF M10 BASEPLATE SECURING SCREWS EQUALLY SPACED ON CENTRES ON #385 (#15.16") P.C.

SEE TABLE FOR SPIGOT DIA.

SEE TABLE FOR HOLE DETAILS

BASEPLATE DETAILS		
	SPIGOT DIA.	HOLE DETAILS (22.5" OFF CENTRES)
F25	#199.95 -0.05 (#7.872" -0.002")	8 HOLES M16x20 (0.79") DEEP ON #254.0 (#10.00") P.C.
FA25	#152.25 -0.05 (#5.994" -0.002")	8 HOLES 5/8"UNCx20 (0.79") DEEP ON #254.0 (#10.00") P.C.

MAX BORE RECTANGULAR KEY		
STD	BORE	KEY
BS4235	76.0	22 x 14
BS46	3.000"	3/4" x 1/2"
ANSI B17.1	3.000"	3/4" x 1/2"

MAX BORE SQUARE KEY		
STD	BORE	KEY
BS4235	-	-
BS46	2.750"	3/4"SQ
ANSI B17.1	2.750"	5/8"SQ

MAX ACME THREAD = 3.3/8"

IB10AS6 BEVEL / SPUR COMBINATION GEARBOX, 8, 12, 16, 18, 24, 32, 36 & 48:1 RATIO, MANUAL INPUT, F25 BASEPLATE

DETAILS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

FOR UP TO DATE DETAILS VISIT www.rotork.com



Regina House
Ring Road
Bramley
Leeds
LS13 4ET
United Kingdom

DRAWING No	IB10AS6
ISSUE	1
DATE	20/01/03