



BASEPLATE DETAILS		
	SPIGOT DIA.	HOLE DETAILS (22.5° OFF CENTRES)
F35	$\#259.95 -0.05$ $(\#10.234'' -0.002'')$	8 HOLES M30x40 (1.57'') DEEP ON $\#356.0 (\#14.02'')$ P.C.
FA35	$\#215.80 -0.25$ $(\#8.496'' -0.008'')$	8 HOLES 1"UNCx40 (1.57'') DEEP ON $\#355.6 (\#14.00'')$ P.C.
AM35	$\#259.95 -0.05$ $(\#10.234'' -0.002'')$	8 HOLES 1.25" UNCx40 (1.57'') DEEP ON $\#356.0 (\#14.02'')$ P.C.

MAX BORE RECTANGULAR KEY			MAX BORE SQUARE KEY		
STD	BORE	KEY	STD	BORE	KEY
BS4235	121.0	32 x 18	BS4235	-	-
BS46	4.625"	1.1/4" x 7/8"	BS46	4.250"	1.1/4" SQ
ANSI B17.1	4.625"	1.1/4" x 7/8"	ANSI B17.1	4.500"	1" SQ

MAX ACME THREAD = 4.5/8"

IB13AS8 BEVEL / SPUR COMBINATION GEARBOX, 32, 36, 48, 60, 64, 72, 80, 90, 96 & 120:1 RATIO, MANUAL INPUT, F35/FA35/AM35 BASEPLATE

DETAILS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

FOR UP TO DATE DETAILS VISIT www.rotork.com



Regina House
 Ring Road
 Bramley
 Leeds
 LS13 4ET
 United Kingdom

DRAWING No

IB13AS8

ISSUE

2

DATE

20/01/03